

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ACTELLIC 050 EC
Design code : A5832C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Insecticide

1.3 Details of the supplier of the safety data sheet

Company : Syngenta Crop Protection AG
Rosentalstrasse 67, Postfach
CH-4002 Basel
Switzerland

Telephone : +41 61 323 11 11

Telefax : +41 61 323 12 12

E-mail address of person responsible for the SDS : sds.ch@syngenta.com

1.4 Emergency telephone number

Emergency telephone number : +44 1484 538444

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 1	H370: Causes damage to organs.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Short-term (acute) aquatic hazard,	H400: Very toxic to aquatic life.


ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

Category 1
Long-term (chronic) aquatic hazard,
Category 1 H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H370 Causes damage to organs.
H410 Very toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH401 To avoid risks to human health and the environment, comply with the instructions for use.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

pirimiphos-methyl (ISO)
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified
calcium dodecylbenzenesulphonate
2-methylpropan-1-ol

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version
18.0

Revision Date:
12.08.2020

SDS Number:
S176502012

This version replaces all previous versions.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

This product contains an anticholinesterase compound. Do not use if under medical advice not to work with such compounds.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
pirimiphos-methyl (ISO)	29232-93-7 249-528-5 015-134-00-5	Acute Tox. 4; H302 STOT SE 1; H370 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1,000 M-Factor (Chronic aquatic toxicity): 1,000	>= 30 - < 50
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
1,2,4-trimethylbenzene	95-63-6 202-436-9 601-043-00-3	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
calcium dodecylbenzenesulphonate	26264-06-2 247-557-8	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 3 - < 10
4-methylpentan-2-one	108-10-1 203-550-1 606-004-00-4 01-2119473980-30	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335	>= 1 - < 10
2-methylpropan-1-ol	78-83-1 201-148-0 603-108-00-1	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 1 - < 3

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

	01-2119484609-23	STOT SE 3; H336 STOT SE 3; H335	
--	------------------	------------------------------------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Have the product container, label or Safety Data Sheet with you when calling the emergency number, a poison control center or physician, or going for treatment.
- If inhaled : Move the victim to fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Keep patient warm and at rest.
Call a physician or poison control centre immediately.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with plenty of water.
If skin irritation persists, call a physician.
Wash contaminated clothing before re-use.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Immediate medical attention is required.
- If swallowed : If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Poisoning produces effects associated with anticholinesterase activity which may include:
Nausea
Diarrhoea
Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Consider taking venous blood for determination of blood cholinesterase activity (use heparin tube).
Administer atropine sulphate as antidote.
Specific antidotes are oximes (e.g. Pralidoxime) or Toxogonin.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Extinguishing media - small fires
Use water spray, alcohol-resistant foam, dry chemical or

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

carbon dioxide.
Extinguishing media - large fires
Alcohol-resistant foam

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.
Flash back possible over considerable distance.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.
Further information : Do not allow run-off from fire fighting to enter drains or water courses.
Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Keep people away from and upwind of spill/leak.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Remove all sources of ignition.
Pay attention to flashback.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Clean with detergents. Avoid solvents.
Retain and dispose of contaminated wash water.

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

6.4 Reference to other sections

For disposal considerations see section 13., Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes.
When using do not eat, drink or smoke.
Use only in an area containing flame proof equipment.
Take precautionary measures against static discharges.
For personal protection see section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from combustible material. Keep in an area equipped with sprinklers. Keep away from food, drink and animal feedingstuffs. No smoking.

Further information on storage stability : Physically and chemically stable for at least 2 years when stored in the original unopened sales container at ambient temperatures.

7.3 Specific end use(s)

Specific use(s) : For proper and safe use of this product, please refer to the approval conditions laid down on the product label.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
pirimiphos-methyl (ISO)	29232-93-7	TWA	3 mg/m ³ (Skin)	Syngenta
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6	TWA	19 ppm 100 mg/m ³	Supplier
1,2,4-trimethylbenzene	95-63-6	TWA	20 ppm 100 mg/m ³	2000/39/EC
	Further information: Indicative			
	95-63-6	TWA	20 ppm 100 mg/m ³	CH SUVA
	Further information: Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version
18.0

Revision Date:
12.08.2020

SDS Number:
S176502012

This version replaces all previous versions.

	95-63-6	STEL	40 ppm 200 mg/m ³	CH SUVA
4-methylpentan-2-one	108-10-1	TWA	20 ppm 83 mg/m ³	2000/39/EC
Further information: Indicative				
	108-10-1	STEL	50 ppm 208 mg/m ³	2000/39/EC
	108-10-1	TWA	20 ppm 82 mg/m ³	CH SUVA
Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, Deutsche Forschungsgemeinschaft, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected				
	108-10-1	STEL	40 ppm 164 mg/m ³	CH SUVA
2-methylpropan-1-ol	78-83-1	TWA	50 ppm 150 mg/m ³	CH SUVA
Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected				
	78-83-1	STEL	50 ppm 150 mg/m ³	CH SUVA

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
4-methylpentan-2-one	108-10-1	4-methylpentan-2-one: 20 micromol per litre (Urine)	Immediately after exposition or after working hours	CH BAT
		4-methylpentan-2-one: 2 mg/l (Urine)	Immediately after exposition or after working hours	CH BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	Workers	Inhalation	Long-term systemic effects	150 mg/m ³
	Workers	Dermal	Long-term systemic effects	25 mg/kg
	Consumers	Inhalation	Long-term systemic effects	32 mg/m ³
	Consumers	Dermal	Long-term systemic effects	11 mg/kg
	Consumers	Oral	Long-term systemic effects	11 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version
18.0

Revision Date:
12.08.2020

SDS Number:
S176502012

This version replaces all previous versions.

calcium dodecylbenzenesulphonate	Workers	Dermal	Long-term systemic effects	1.7 mg/kg
	Consumers	Dermal	Acute systemic effects	85 mg/kg
	Consumers	Oral	Long-term local effects	89 mg/kg
2-methylpropan-1-ol	Workers	Inhalation	Long-term systemic effects, Long-term local effects	310 mg/m3
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	55 mg/m3
	Consumers	Oral	Long-term systemic effects, Long-term local effects	25 mg/kg
4-methylpentan-2-one	Workers	Inhalation	Long-term systemic effects	83 mg/m3
	Workers	Inhalation	Acute systemic effects	208 mg/m3
	Workers	Inhalation	Long-term local effects	83 mg/m3
	Workers	Inhalation	Acute local effects	208 mg/m3
	Workers	Dermal	Long-term systemic effects	11.8 mg/kg
	Consumers	Inhalation	Long-term systemic effects	14.7 mg/m3
	Consumers	Inhalation	Acute systemic effects	155.2 mg/m3
	Consumers	Inhalation	Long-term local effects	14.7 mg/m3
	Consumers	Inhalation	Acute local effects	155.2 mg/m3
	Consumers	Dermal	Long-term systemic effects	4.2 mg/kg
	Consumers	Oral	Long-term systemic effects	4.2 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
calcium dodecylbenzenesulphonate	Fresh water	0.023 mg/l
	Marine water	0.0023 mg/l
	Intermittent use/release	0.01 mg/l
	Fresh water sediment	0.174 mg/kg
	Marine sediment	0.0174 mg/kg
	Sewage treatment plant	3 mg/kg
	Soil	0.62 mg/kg
2-methylpropan-1-ol	Fresh water	0.4 mg/l
	Sewage treatment plant	10 mg/l
	Soil	0.0699 mg/kg
	Marine sediment	0.152 mg/kg
	Fresh water sediment	1.52 mg/kg
	Marine water	0.04 mg/l

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

4-methylpentan-2-one	Fresh water	0.6 mg/l
	Marine water	0.06 mg/l
	Freshwater - intermittent	1.5 mg/l
	Sewage treatment plant	27.5 mg/l
	Fresh water sediment	8.27 mg/kg
	Marine sediment	0.83 mg/kg
	Soil	1.3 mg/kg

8.2 Exposure controls

Engineering measures

Containment and/or segregation is the most reliable technical protection measure if exposure cannot be eliminated.

The extent of these protection measures depends on the actual risks in use.

Maintain air concentrations below occupational exposure standards.
Where necessary, seek additional occupational hygiene advice.

Personal protective equipment

Eye protection : Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Tightly fitting safety goggles
Face-shield
Equipment should conform to EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0.5 mm

Remarks : Wear protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Remove and wash contaminated clothing before re-use.
Wear as appropriate:

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

- Respiratory protection : Impervious clothing
: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Suitable respiratory equipment:
Respirator with combination filter for vapour/particulate (EN 141)
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Filter type : Combined particulates and organic vapour type (A-P)
- Protective measures : The use of technical measures should always have priority over the use of personal protective equipment.
When selecting personal protective equipment, seek appropriate professional advice.
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid, clear
Colour : light yellow to brown
- Odour : aromatic
Odour Threshold : No data available
- pH : 4 - 8
Concentration: 1 % w/v
- Melting point/range : No data available
- Boiling point/boiling range : No data available
- Flash point : 46 °C
Method: Pensky-Martens closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Density : 1.02 g/cm³ (25 °C)

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

Solubility(ies)
Solubility in other solvents : Miscible
Solvent: Water

Partition coefficient: n-octanol/water : No data available
Auto-ignition temperature : 410 °C

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : 4.61 mPa.s (40 °C)
8.08 mPa.s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Surface tension : 35.3 mN/m, 25 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure :
Ingestion
Inhalation
Skin contact
Eye contact

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat, female): > 300 - 2,000 mg/kg
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Components:

pirimiphos-methyl (ISO):

Acute oral toxicity : LD50 (Rat, male and female): 1,414 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.04 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Acute oral toxicity : LD50 (Rat): 3,952 mg/kg

1,2,4-trimethylbenzene:

Acute inhalation toxicity : LC50 (Rat): 11 mg/l
Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

4-methylpentan-2-one:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

short term inhalation.

2-methylpropan-1-ol:

Acute oral toxicity : LD50 (Rat): 2,830 - 3,350 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 2,460 mg/kg

Skin corrosion/irritation

Product:

Species : Rabbit
Result : No skin irritation

Components:

pirimiphos-methyl (ISO):

Species : Rabbit
Result : No skin irritation

1,2,4-trimethylbenzene:

Assessment : Irritating to skin.

calcium dodecylbenzenesulphonate:

Result : Irritating to skin.

2-methylpropan-1-ol:

Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Species : Rabbit
Result : Risk of serious damage to eyes.

Components:

pirimiphos-methyl (ISO):

Species : Rabbit
Result : No eye irritation

1,2,4-trimethylbenzene:

Assessment : Irritating to eyes.

calcium dodecylbenzenesulphonate:

Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version
18.0

Revision Date:
12.08.2020

SDS Number:
S176502012

This version replaces all previous versions.

4-methylpentan-2-one:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

2-methylpropan-1-ol:

Result : Risk of serious damage to eyes.

Respiratory or skin sensitisation

Product:

Test Type : Buehler Test
Species : Guinea pig
Result : May cause sensitisation by skin contact.

Components:

pirimiphos-methyl (ISO):

Species : Guinea pig
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Components:

pirimiphos-methyl (ISO):

Germ cell mutagenicity-
Assessment : Animal testing did not show any mutagenic effects.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Germ cell mutagenicity-
Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Components:

pirimiphos-methyl (ISO):

Carcinogenicity -
Assessment : No evidence of carcinogenicity in animal studies.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Carcinogenicity -
Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Components:

pirimiphos-methyl (ISO):

Reproductive toxicity -
Assessment : No toxicity to reproduction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version
18.0

Revision Date:
12.08.2020

SDS Number:
S176502012

This version replaces all previous versions.

STOT - single exposure

Components:

pirimiphos-methyl (ISO):

Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

1,2,4-trimethylbenzene:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

4-methylpentan-2-one:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

2-methylpropan-1-ol:

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

pirimiphos-methyl (ISO):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

May be fatal if swallowed and enters airways.

1,2,4-trimethylbenzene:

May be fatal if swallowed and enters airways.

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

SECTION 12: Ecological information

12.1 Toxicity

Product:

- Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 6.2 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.00048 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 8.27 mg/l
Exposure time: 72 h
- NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.22 mg/l
End point: Growth rate
Exposure time: 72 h

Components:

pirimiphos-methyl (ISO):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.404 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.000314 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 3.38 mg/l
Exposure time: 72 h
- NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.3 mg/l
End point: Growth rate
Exposure time: 72 h
- M-Factor (Acute aquatic toxicity) : 1,000
- Toxicity to microorganisms : IC50 (Pseudomonas putida): > 4.5 mg/l
Exposure time: 6 h
- Toxicity to fish (Chronic toxicity) : NOEC: < 0.025 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.00005 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version
18.0

Revision Date:
12.08.2020

SDS Number:
S176502012

This version replaces all previous versions.

M-Factor (Chronic aquatic toxicity) : 1,000

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.2 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 2.6 - 2.9 mg/l
Exposure time: 72 h
Test Type: Growth inhibition

NOEC (Raphidocelis subcapitata (freshwater green alga)): 1 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 1.23 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2.14 mg/l
Exposure time: 28 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,2,4-trimethylbenzene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 7.72 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.6 mg/l
Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

calcium dodecylbenzenesulphonate:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

2-methylpropan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,430 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia pulex (Water flea)): 1,100 mg/l

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): 1,799 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 20 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

pirimiphos-methyl (ISO):

Stability in water : Degradation half life: 4 - 6 d
Remarks: Product is not persistent.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Biodegradability : Result: Readily biodegradable.

2-methylpropan-1-ol:

Biodegradability : Result: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

pirimiphos-methyl (ISO):

Bioaccumulation : Remarks: High bioaccumulation potential.

Partition coefficient: n-octanol/water : Pow: 3.9 (20 °C)
pH: 4

Pow: 4.2 (20 °C)
pH: 5 - 7

12.4 Mobility in soil

Components:

pirimiphos-methyl (ISO):

Distribution among environmental compartments : Remarks: Low mobility in soil.

Stability in soil : Dissipation time: 8.3 d
Percentage dissipation: 50 % (DT50)
Remarks: Product is not persistent.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

pirimiphos-methyl (ISO):

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

4-methylpentan-2-one:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

2-methylpropan-1-ol:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.
Where possible recycling is preferred to disposal or incineration.
If recycling is not practicable, dispose of in compliance with local regulations.
- Contaminated packaging : Empty remaining contents.
Triple rinse containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1993
ADR : UN 1993
RID : UN 1993
IMDG : UN 1993
IATA : UN 1993

14.2 UN proper shipping name

ADN : FLAMMABLE LIQUID, N.O.S.
(METHYL ISOBUTYL KETONE AND SOLVENT NAPHTHA)
ADR : FLAMMABLE LIQUID, N.O.S.
(METHYL ISOBUTYL KETONE AND SOLVENT NAPHTHA)
RID : FLAMMABLE LIQUID, N.O.S.
(METHYL ISOBUTYL KETONE AND SOLVENT NAPHTHA)
IMDG : FLAMMABLE LIQUID, N.O.S.
(METHYL ISOBUTYL KETONE AND SOLVENT NAPHTHA)
IATA : Flammable liquid, n.o.s.
(METHYL ISOBUTYL KETONE AND SOLVENT NAPHTHA)

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)
RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30

ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3
1,2,4-trimethylbenzene
4-methylpentan-2-one
xylene
cumene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable
REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
PIC Ordinance, ChemPICO (814.82) : Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t
E1	ENVIRONMENTAL HAZARDS	100 t	200 t

Other regulations:

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2): Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance when it is used in the specified applications.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H370	: Causes damage to organs.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
CH BAT	: Switzerland. List of BAT-values
CH SUVA	: Switzerland. Limit values at the work place
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
CH SUVA / TWA	: Time Weighted Average
CH SUVA / STEL	: Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ACTELLIC 050 EC

Version 18.0 Revision Date: 12.08.2020 SDS Number: S176502012 This version replaces all previous versions.

PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H302
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 1	H370
STOT SE 3	H336
STOT SE 3	H335
Asp. Tox. 1	H304
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Based on product data or assessment
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN